

Issuing Date 05-Jan-2015

Revision date 01-Jun-2018

### **1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

PROSOCO

Revision Number 3

Product identifier Product Name

Paver Kare® Paver Enhancer

Other means of identification Product Code(s) UN number

56070 UN1866

Recommended use of the chemical and restrictions on useRecommended useRestricted to professional users.Uses advised againstNo information available

Details of the supplier of the safety data sheet Manufacturer Address PROSOCO, Inc. 3741 Greenway Circle Lawrence, Kansas 66046 Emergency telephone number 8:00 AM – 5:00 PM CST Monday-Friday NON-BUSINESS HOURS (INFOTRAC)


785-865-4200 800-535-5053

### 2. HAZARDS IDENTIFICATION

#### **Classification**

Skin corrosion/irritation	Category 2
Carcinogenicity	Category 2
Reproductive toxicity	Category 1B
Aspiration hazard	Category 1
Flammable liquids	Category 3

### Label elements



Appearance clear

Physical state Liquid

Odor Petroleum

### **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Keep away from heat/sparks/open flames/hot surfaces. — No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/ /equipment Use only non-sparking tools Take precautionary measures against static discharge

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention If skin irritation occurs: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting In case of fire: Use CO2, dry chemical, or foam for extinction

### **Precautionary Statements - Storage**

Store locked up Store in a well-ventilated place. Keep cool

#### Precautionary Statements - Disposal Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Other information

### May be harmful if swallowed

· May be harmful in contact with skin

20.7559% of the mixture consists of ingredient(s) of unknown toxicity

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical name	CAS No.	Weight-%	Trade Secret
Mineral Spirits	64742-88-7	40 - 70	*
Stoddard Solvent	8052-41-3	3 - 7	*
1,2,4-trimethylbenzene	95-63-6	1 - 5	*
Isobutyl triethoxysilane	18395-30-7	1 - 5	*
Xylene	1330-20-7	1 - 5	*
Cumene	98-82-8	0.1 - 1	*
Ethylbenzene	100-41-4	0.1 - 1	*
Dibutyltin Dilaurate	77-58-7	0.1 - 1	*

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

#### Description of first aid measures

General advice	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

	continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.		
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.		
Inhalation	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a physician.		
Ingestion	Do NOT induce vomiting. Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician.		
Self-protection of the first aider	Remove all sources of ignition. Use personal protective equipment as required.		
Most important symptoms and effe	cts, both acute and delayed		
SymptomsMay cause irritation. May be fatal if swallowed and enters airways.			
Indication of any immediate medical attention and special treatment needed			
Note to physicians	Treat symptomatically.		

# 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Use. Dry chemical. Carbon dioxide (CO2). Water spray (fog). Alcohol resistant foam.

**Unsuitable Extinguishing Media** Caution: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

Keep away from heat. Keep product and empty container away from heat and sources of ignition. Risk of ignition.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure adequate ventilation, especially in confined areas. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take precautionary measures against static discharges. Use personal protective equipment as required.				
Environmental precautions					
Environmental precautions	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional ecological information.				
Methods and material for containme	Methods and material for containment and cleaning up				
Methods for containment	Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later disposal.				
Methods for cleaning up	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges. Use only non-sparking tools. Ground and bond containers when transferring material.				

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling	Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use with local exhaust ventilation. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use personal protective equipment as required. Avoid breathing vapors or mists. Do not eat, drink or smoke when using this product.			
Conditions for safe storage, including any incompatibilities				
Storage Conditions	Keep containers tightly closed in a cool, well-ventilated place. Keep in properly labeled containers. Keep away from heat. Keep out of the reach of children.			

Incompatible materials Incompatible with oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### **Exposure Guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Stoddard Solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m³ Ceiling: 1800 mg/m³ 15 min TWA: 350 mg/m³
1,2,4-trimethylbenzene 95-63-6			TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m <sup>3</sup>
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
Dibutyltin Dilaurate 77-58-7	STEL: 0.2 mg/m <sup>3</sup> Sn TWA: 0.1 mg/m <sup>3</sup> Sn S*	TWA: 0.1 mg/m³ Sn (vacated) TWA: 0.1 mg/m³ Sn (vacated) S*	IDLH: 25 mg/m³ Sn TWA: 0.1 mg/m³ except Cyhexatin Sn

NIOSH IDLH Immediately Dangerous to Life or Health

### Other information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### Appropriate engineering controls

#### **Engineering Controls**

Showers Eyewash stations Ventilation systems.

### Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective gloves and protective clothing.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Appearance Color	Liquid clear Caramel	Odor Odor threshold	Petroleum No information available
<u>Property</u> pH	<u>Values</u> Not Applicable	Remarks • Method	
Melting point / freezing point °F	-30 °C / -22 °F		
Boiling point / boiling range Flash point	No information available 39 °C / 102 °F	ASTM D 5095	
Evaporation rate	No information available		
Flammability (solid, gas) Flammability Limit in Air	No information available		
Upper flammability limit: Lower flammability limit:	No information available No information available		
Vapor pressure Vapor density	No information available No information available		
Specific gravity	0.871		
Water solubility Solubility in other solvents Partition coefficient	negligible No information available No information available		
Autoignition temperature	No information available		
Decomposition temperature Kinematic viscosity	No information available No information available		
Dynamic viscosity	No information available		

# **10. STABILITY AND REACTIVITY**

### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Heat, flames and sparks.

### Incompatible materials

Incompatible with oxidizing agents.

#### Hazardous decomposition products

Carbon oxides. Unidentified organic compounds.

### **11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Product Information		May be fatal if swallowed and enters airways May cause irritation
	Inhalation	Avoid breathing vapors or mists. May be fatal if inhaled.
	Eye contact	Avoid contact with eyes. May cause irritation.
	Skin Contact	Avoid contact with skin. May cause irritation.
	Ingestion	Do not taste or swallow. May be fatal if swallowed.

#### **Component Information**

Chemical name	LD50/Oral	LD50/Dermal	Inhalation LC50
Mineral Spirits 64742-88-7	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat)4 h
1,2,4-trimethylbenzene 95-63-6	= 3400 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m³ (Rat)4 h
Xylene 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 5000 ppm (Rat)4 h = 47635 mg/L (Rat)4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 39000 mg/m³(Rat)4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat)4 h
Dibutyltin Dilaurate 77-58-7	= 175 mg/kg (Rat)		

### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

May be fatal if swallowed and enters airways. may cause eye and skin irritation.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

(	Sensitization Germ cell mutagenicity Carcinogenicity	No information available. No information available. The table below indicates whether each agency has listed any ingredient as a carcinogen. This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).			d by IARC as
Chemical name ACGIH IARC				NTP	OSHA
	Xylene	-	Group 3	-	-

Xylene	-	Group 3	-	-
1330-20-7				
Cumene 98-82-8	-	Group 2B	-	Х
Ethylbenzene 100-41-4	A3	Group 2B	-	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

No information available.

**Reproductive toxicity** STOT - single exposure No information available.

STOT - repeated exposure No information available.

Target organ effects

central nervous system, Eyes, kidney, Respiratory system, Skin, blood, heart, liver.

Aspiration hazard

May be fatal if swallowed and enters airways.

### Numerical measures of toxicity - Product Information

Unknown acute toxicity20.7559% of the mixture consists of ingredient(s) of unknown toxicityThe following values are calculatedbased on chapter 3.1 of the GHS document .ATEmix (oral)3404 mg/kgATEmix (dermal)3273 mg/kg mg/lATEmix (inhalation-dust/mist)11.1 mg/l

## **12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Mineral Spirits 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static	-	100: 48 h Daphnia magna mg/L EC50
1,2,4-trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	-	6.14: 48 h Daphnia magna mg/L EC50
Xylene 1330-20-7	-	<ul> <li>13.4: 96 h Pimephales promelas mg/L LC50</li> <li>flow-through 2.661 - 4.093:</li> <li>96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3:</li> <li>96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h</li> <li>Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static</li> </ul>		3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
Cumene 98-82-8	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	-	0.6: 48 h Daphnia magna mg/L EC50 7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static
Ethylbenzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	-	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
Dibutyltin Dilaurate 77-58-7	-	2: 48 h Oryzias latipes mg/L LC50	-	-

## Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

Chemical name	Partition coefficient
1,2,4-trimethylbenzene 95-63-6	3.63
Xylene 1330-20-7	3.15
Cumene 98-82-8	3.55
Ethylbenzene 100-41-4	3.118

Other adverse effects

No information available

## 13. DISPOSAL CONSIDERATIONS

Waste treatment methods	
Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
US EPA Waste Number	D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

# **14. TRANSPORT INFORMATION**

DOT UN number UN proper shipping name Transport hazard class(es) Packing group	Not regulated (If shipped in NON BULK packaging by ground transport) UN1866 Resin Solution 3 III
IATA UN number UN proper shipping name Transport hazard class(es) Packing group	UN1866 Resin Solution 3 III
IMDG UN number UN proper shipping name Transport hazard class(es) Packing group	UN1866 Resin Solution 3 III

# **15. REGULATORY INFORMATION**

Internationa	I Inventories
TSCA	
DSL/NDSL	
Lawawala	

Complies Complies

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

### US Federal Regulations

### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
1,2,4-trimethylbenzene - 95-63-6	95-63-6	1 - 5	1.0
Xylene - 1330-20-7	1330-20-7	1 - 5	1.0
Ethylbenzene - 100-41-4	100-41-4	0.1 - 1	0.1
SARA 311/312 Hazard Categories			
Acute health hazard	Yes		
Chronic Health Hazard	No		
Fire hazard	Yes		
Sudden release of pressure hazard	No		
Reactive Hazard	No		

### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	Х
Ethylbenzene 100-41-4	1000 lb	Х	Х	Х

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb	-	RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Cumene	5000 lb	-	RQ 5000 lb final RQ
98-82-8			RQ 2270 kg final RQ
Ethylbenzene	1000 lb	_	RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

### US State Regulations

California Proposition 65

### U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Mineral Spirits 64742-88-7	Х	-	-
Stoddard Solvent	Х	X	Х

### 56070 Paver Kare® Paver Enhancer

8052-41-3			
1,2,4-trimethylbenzene 95-63-6	Х	X	Х
Xylene 1330-20-7	Х	Х	Х
Cumene 98-82-8	Х	Х	Х
Ethylbenzene 100-41-4	Х	Х	Х

### **16. OTHER INFORMATION**

NFPA	Health hazards 2	Flammability 2	Instability 0	Physical and chemical properties -
HMIS	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection X
Prepared By	Regulato	ry Department		
Issuing Date	05-Jan-2	015		
Revision date	01-Jun-2	018		
Revision Note				
SDS sections updated				
2467811				
For product produced af	ter June 15, 2018			
Disclaimer	·			
The information contai	ned on the Cofety Date	Chaot has been compil	lad from data conciderad o	agurata. This data is

The information contained on the Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described. This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

End of Safety Data Sheet