

# PRODUCT SUBMITTAL

WIRE-BOND

## Bond-N-Flash Mastic



**Description :** BOND-N-FLASH Mastic is an all weather butyl mastic specifically formulated to permanently seal all laps, seams and terminations in the application of BOND-N-FLASH stainless steel membrane flashing. BOND-N-FLASH mastic may be applied to concrete, brick, stone, metal, wood, PVC and most plastics and painted surfaces.

**Uses:** Used primarily as a secondary seal on horizontal and vertical seams, overlaps, punctures, other terminations such as end dams or protrusions.

### Features:

- Excellent resistance to weathering, shrinking and cracking
- Excellent strength and flexibility
- Resistant to U.V. degradation
- Withstands a wide range of high heat and extreme cold from -20 degrees F to 200 Degrees F
- Application temperatures are 0 Degrees F to 120 Degrees F
- Can be painted

Corporate Office: 400 Rountree Rd Charlotte, NC 28217  
TEL: (800) 849-6722 FAX: (704) 525-3761

Mailing Address: P.O. Box 240988 Charlotte, NC 28224

WIRE-BOND

[www.wirebond.com](http://www.wirebond.com)

Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113  
TEL: (800) 441-8359 FAX: (901) 775-9449

Mailing Address: P.O. Box 13124 Memphis, TN 38113

# PRODUCT SUBMITTAL



WIRE-BOND

## Bond-N-Flash MASTIC

**Application:** Apply **BOND-N-FLASH** Mastic on a surface that is dry, clean and free of dust. Do not solvent wipe substrate with either alcohol or oil-containing solvents. Mineral Spirits may be used. Surface should be dry before applying the **BOND-N-FLASH** Mastic. Apply the mastic either by trowel or caulking gun onto a dry surface. If applied with a caulking gun, strike the bead of with a trowel to about ¼" in thickness and ½" to 1 inch in width.

On the bottom edge of vertical applications, **BOND-N-FLASH** Mastic should be troweled upward. **BOND-N-FLASH** Mastic should be used liberally around protrusions, laps and other areas requiring patch pieces.

**Coverage:** The amount of **BOND-N-FLASH** Mastic will vary widely from job to job. One gallon of **BOND-N-FLASH** Mastic one (1) inches wide by one-quarter (1/4) inch thick will yield approximately 100 lineal feet of coverage.

### **Packaging:**

Available in five ( 5 ) gallon pails

Available in 30 oz. cartridge

**Storage:** If stored in original unopened container at or below 90 degrees F, shelf life is 12 months from date of shipment. Average storage temperatures opened 65 – 110 degrees F. Do not store in direct sunlight.

**Safety:** Use with adequate ventilation. Inhalation of vapors may cause slight eye or throat irritation. See MSDS for additional information

Corporate Office: 400 Rountree Rd Charlotte, NC 28217  
TEL: (800) 849-6722 FAX: (704) 525-3761

Mailing Address: P.O. Box 240988 Charlotte, NC 28224



[www.wirebond.com](http://www.wirebond.com)

Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113  
TEL: (800) 441-8359 FAX: (901) 775-9449

Mailing Address: P.O. Box 13124 Memphis, TN 38113